

Material Safety Data Sheet according 91/155/EEC

Product Name : 1213K....

Date: 15.06.07

Revision date: 22.06.06

page: 1/6

1. IDENTIFICATION OF THE PREPARATION AND COMPANY.

Product Name and Code :

1213K.... bunt  
glänzend, lufttrocknend

Use of the substance/preparation:

Name of the company:

Germany

Phone of the company:

Emergency phone :

10R2 11HW BPP



14

2. COMPOSITION/INFORMATION ON INGREDIENTS.

Chemical family: Alkydharz-Kombination

Substances presenting a health or environmental hazard:

EINECS-No.	Names	Symb.	Conc.
215-535-7	R-phrases xylene, mixture of isomers 10-20/21-38	Xn	5 - 12.6
203-604-4	1,3,5-trimethylbenzene, mesitylene 10-37-51/53	Xi,N	< 0.5
202-496-6	2-butanone oxime 21-40-41-43	Xn	< 0.5
202-436-9	1,2,4-trimethylbenzene 10-20-36/37/38-51/53	Xn,N	0.5 - 1
215-693-7	C.I. Pigment Yellow 34 61-33-40-50/53-62	T,N	12.6 - 25
270-066-5	Fettsäure, C6-19-verzweigt, Kobalt(2+)seife 22-38-43-51/53	Xn,N	< 0.5
265-199-0	Lösungsmittelnaphta, leichte aromatische 10-37-51/53-65-66-67	Xn,N	5 - 12.6

See full text of phrases under chapter 16.

3. HAZARDS IDENTIFICATION OF THE PREPARATION.

Danger classification : T Toxic  
N Dangerous for the environment

10	Flammable.
33	Danger of cumulative effects.
40	Limited evidence of a carcinogenic effect.
51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
61	May cause harm to the unborn child.
62	Possible risk of impaired fertility.

4. FIRST AID MEASURES.

General :

In all cases of doubt, or when symptoms persist, seek medical attention.  
Never give anything by mouth to an unconscious person.

Inhalation :

Remove to fresh air, keep patient warm and at rest, if breathing is irregular or stopped, administer artificial respiration. Give nothing by mouth. If unconscious place in recovery position and seek medical advice.

**Eye contact :**

Remove contact lenses, irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart and seek medical advice.

**Skin contact :**

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do not use solvents or thinners.

**Ingestion :**

If accidentally swallowed obtain immediate medical attention. Keep at rest. Do not induce vomiting.

**5. FIRE-FIGHTING MEASURES.**

**Extinguishing media:**

Recommended: alcohol resistant foam, CO<sub>2</sub>, powders, waterspray.

Not to be used: waterjet.

**Recommendations:**

Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Appropriate breathing apparatus may be required. Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses.

**6. ACCIDENTAL RELEASE MEASURES.**

Exclude sources of ignition and ventilate the area. Avoid breathing vapours. Refer to protective measures listed in sections 7 and 8. Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Do not allow to enter drains or watercourses.

Clean preferably with a detergent; avoid use of solvents.

If the product contaminates lakes, rivers or sewages, inform appropriate authorities in accordance with local regulations.

**7. HANDLING AND STORAGE.**

**Handling.**

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits.

In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard.

Preparation may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear anti-static footwear and clothing and floors should be of the conducting type.

Keep container tightly closed. Isolate from sources of heat, sparks and open flame. No sparking tools should be used.

Avoid skin and eye contact. Avoid inhalation of dust, particulates and spray mist arising from the application of this preparation. Avoid inhalation of dust from sanding.

Smoking, eating and drinking should be prohibited in application area.

For personal protection see Section 8.

Never use pressure to empty: container is not a pressure vessel.

Always keep in containers of same material as the original one.

Comply with the health and safety at work laws.

**Storage.**

Although the storage and use of this product is not subject to specific statutory requirements, observation of the principles of the Highly Flammable Liquids and Liquefied Petroleum Gases Regulations as appropriate will be seen as good industrial practice in meeting the general duties of the Health and Safety at Work Act.

Observe label precautions. Store between 15 and 30 °C in a dry, well ventilated place away from sources of heat and direct sunlight.

Keep away from sources of ignition. Keep away from oxidizing agents, from strongly alkaline and strongly acid materials.

No smoking. Prevent unauthorized access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION.****Engineering Measures.**

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

**Exposure Limits.**

Occupational exposure limit for :

EINECS-No. Names

215-535-7 xylene, mixture of isomers

STEL

LTEL

150.000 100.000 ppm

**Personal Protection.****Respiratory protection:**

If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators.

**Hand protection:**

For prolonged or repeated handling, use Polychloropren gloves.

Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred.

**Eye protection:**

Use safety eyewear designed to protect against splash of liquids.

**Skin protection:**

Personnel should wear anti-static clothings made of natural fibre or of high temperature resistant synthetic fiber.

**9. PHYSICAL AND CHEMICAL PROPERTIES.****General information**

appearance : liquid  
colour : siehe Etikett  
odour : arttypisch

**Important health, safety and environmental information**

Flash point : 26 °C  
Ignition temperature : 201 °C  
Lower explosion limit : 0.6 Vol.%  
Upper explosion limit : 12.0 Vol.%  
Vapour pressure at 20 °C: 2 mbar  
Specific gravity at 20 °C: 1.18 g/cm<sup>3</sup>  
Water solubility :  
Viscosity at 20 °C: 90 s 4 mm  
Solvent-separation test : < 3 %  
Percent volatile by weight : 39 %

DIN 53211  
ADR/RID

**10. STABILITY AND REACTIVITY.**

Stable under recommended storage and handling conditions (See section 7).  
When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen etc. Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

keine, bei sachgemäßer Verwendung

keine, bei sachgemäßer Verwendung

keine, bei sachgemäßer Verwendung

**11. TOXICOLOGICAL INFORMATION.**

There are no data available on the preparation itself. The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified for toxicological hazards accordingly. See Chapter 2 and 15 for details.

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

The liquid splashed in the eyes may cause irritation and reversible damage.

**12. ECOLOGICAL INFORMATION.**

The product should not be allowed to enter drains or water courses.

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and is classified for ecotoxicological properties accordingly. See Section 2 and 15 for details.

**13. DISPOSAL CONSIDERATIONS.**

Do not allow into drains or water courses.

Wastes and emptied containers should be deposited according to the official rules.

Code of waste Waste Designation:

080111 waste paint and varnish containing organic solvents or other dangerous substances

**14. TRANSPORT INFORMATION.**

Transport only in accordance with ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport.

ADR/RID Class: no subject to class 3  
bei Gebinden > 450 l Klasse 3

Hazard label(s): 3

UN-No: 1263

ADR hazard: 30

Transport document name: Paint

Packing group: III

Material Safety Data Sheet according 91/155/EEC

Product Name : 1213K...

Date: 15.06.07

Revision date: 22.06.06

page: 5/6

---

IMDG Class:	n.a.
Hazard label(s):	n.a.
EmS:	n.a.
UN-No:	n.a.
Proper shipping name:	Transport in accordance with the provisions of paragraph 2.3.2.5 of the IMDG Code.
Packing group:	n.a.
IMDG > 30 L:	3
Hazard label(s):	3
EmS:	F-E, S-E
UN-No:	1263
Proper shipping name:	PAINT
Packing group:	III
marine pollutant:	n.a.
ICAO/IATA Class:	3
Hazard label(s):	3
UN No:	1263
Proper shipping name:	Paint
Packing group:	III

---

15. REGULATORY INFORMATION.

In accordance with requirements of the Classification Packaging and Labelling of Dangerous Preparations Regulations (1999/45/EC).

The product is labelled as follows:

**Danger classification :**

T Toxic  
N Dangerous for the environment

**Contains:**

C.I. Pigment Yellow 34

**R-phrases:**

10 Flammable.  
33 Danger of cumulative effects.  
40 Limited evidence of a carcinogenic effect.  
51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
61 May cause harm to the unborn child.  
62 Possible risk of impaired fertility.

**S-phrases:**

36/37 Wear suitable protective clothing and gloves.  
38 In case of insufficient ventilation, wear suitable respiratory equipment.  
45 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).  
51 Use only in well-ventilated areas.  
53 Avoid exposure - obtain special instructions before use.  
61 Avoid release to the environment. Refer to special instructions/safety data sheets.  
23 Do not breathe vapour.

**Special provisions concerning the labelling of preparations:**

99 Contains 2-butanone oxime, Fettsäure, C6-19-verzweigt, Kobalt(2+)seife. May produce an allergic reaction.

---

16. OTHER INFORMATION.

Full text of R-phrases with no. appearing in section 2:

Material Safety Data Sheet according 91/155/EEC

Product Name : 1213K....

Date: 15.06.07

Revision date: 22.06.06

page: 6/6

- 
- |          |  |
|----------|--|
| 10       | Flammable.   |
| 20/21    | Harmful by inhalation and in contact with skin.  |
| 38       | Irritating to skin.  |
| 37       | Irritating to respiratory system.  |
| 51/53    | Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.      |
| 21       | Harmful in contact with skin.  |
| 40       | Limited evidence of a carcinogenic effect.   |
| 41       | Risk of serious damage to eyes.  |
| 43       | May cause sensitisation by skin contact.   |
| 20       | Harmful by inhalation.   |
| 36/37/38 | Irritating to eyes, respiratory system and skin.   |
| 61       | May cause harm to the unborn child.  |
| 33       | Danger of cumulative effects.  |
| 50/53    | Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. |
| 62       | Possible risk of impaired fertility.   |
| 22       | Harmful if swallowed.  |
| 65       | Harmful: may cause lung damage if swallowed.   |
| 66       | Repeated exposure may cause skin dryness or cracking.  |
| 67       | Vapours may cause drowsiness and dizziness.  |

The information of this SDS is based on the present state of our knowledge and on current EU and national laws. The product is not to be used for other purposes than those specified under section 1 without first obtaining written handling instruction. It is always the responsibility of the user to take all necessary steps in order to fulfil the demand laid down in the local rules and legislation. The information in this SDS is meant as a description of the safety requirements of our product: it is not to be considered as a guarantee of the products' properties.

---